

# Specifications

| SECTION SUBJECT          | GL1500SE'91               | GL1500A'91      |
|--------------------------|---------------------------|-----------------|
| <b>ENGINE</b>            |                           |                 |
| Cylinder                 | 6 cylinder                | 6 cylinder      |
| Strokes                  | 4-Stroke                  | 4-Stroke        |
| Cooling                  | Water Cooled              | Water Cooled    |
| Camshaft                 | OHC                       | OHC             |
| Valves per cylinder      | 2                         | 2               |
| Displacement             | 1520cc                    | 1520cc          |
| Lubrication system       | Wet Sump                  | Wet Sump        |
| Carburetor               | 36mm(2)                   | 36mm(2)         |
| Main jet                 | = 158                     | = 158           |
| Slow jet                 | = 60                      | = 60            |
| <b>TRANSMISSION</b>      |                           |                 |
| Transmission type        | Constant Mesh             | Constant Mesh   |
| Transmission speeds      | 5-Speed                   | 5-Speed         |
| Clutch                   | Wet Multi-Plate           | Wet Multi-Plate |
| Shift pattern            | 1-N-2-3-4-5               | 1-N-2-3-4-5     |
| <b>CHASSIS</b>           |                           |                 |
| Fuel tank capacity (Std) | 6.3gal                    | 6.3gal          |
| Air filter type          | Paper                     | Paper           |
| Front Brake              | Double Disc               | Double Disc     |
| Rear Brake               | Single Disc               | Single Disc     |
| Front tire               | 130 70-18 63H             | 130 70-18 63H   |
| Rear tire                | 160 80-16 75H             | 160 80-17 75H   |
| <b>SERVICE TUNING</b>    |                           |                 |
| Ignition type            | Full Transistor           | Full Transistor |
| Spark plug gap           | 0.8-0.9mm (0.031"-0.035") |                 |
| <b>LUBRICATION</b>       |                           |                 |
| Recommended fuel         | 86 + Octane               | 86 + Octane     |
| Engine oil - Pro Honda   |                           |                 |
| GN4 10W40                | 08C35-A141M01             | 08C35-A141M01   |
| GN4 20W50                | 08C35-A251M01             | 08C35-A251M01   |
| Engine oil capacity      |                           |                 |
| After draining           | 3.9qt                     | 3.9qt           |
| After reassembly         | 4.5qt                     | 4.5qt           |
| Coolant type             | 08C50-C321S01             | 08C50-C321S01   |
| Coolant ratio            | 50:50                     | 50:50           |
| Fork oil:                |                           |                 |
| Pro Honda (5W SS-7)      | 08208-0005                | 08208-0005      |
| Pro Honda (10W SS-8)     | 08208-0010                | 08208-0010      |