



2015 INTERCEPTOR SPECIFICATIONS*

ENGINE	
Engine Type	782cc liquid-cooled 90° V-4
Bore And Stroke	72mm x 48mm
Induction	PGM-FI with automatic enrichment circuit, 36mm throttle bodies
Ignition	Computer-controlled digital with three-dimensional mapping and electronic advance
Compression Ratio	11.8:1
Valve Train	VTEC DOHC; four valves per cylinder
DRIVE TRAIN	
Transmission	Close-ratio six-speed
Final Drive	#525 O-ring chain
CHASSIS / SUSPENSION / BRAKES	
Front Suspension	43mm with spring-preload adjustability; 4.3 inches travel
Rear Suspension	Pro Arm single-side swingarm with Pro-Link® single spring-preload and rebound damping adjustability; 4.7 inches travel
Front Brake	Dual full-floating 310 mm discs with four-piston calipers
Rear Brake	Single 256 mm disc
Front Tire	120/70ZR-17 radial
Rear Tire	180/55ZR-17 radial
DIMENSIONS	
Rake	25.5°
Trail	95mm (3.74 inches)
Wheelbase	57.4 inches
Seat Height	31.0 inches to 31.8 inches
Curb Weight	529 pounds (Includes all standard equipment, required fluids and a full tank of fuel-ready to ride)
Fuel Capacity	5.2 gallons
OTHER	
Emissions	Meets current California Air Resources Board (CARB) and EPA standards.
Available Colors	Red, Pearl White
Model Id	VFR800F
FACTORY WARRANTY INFORMATION	
One Year	Transferable, unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan