

TIRES

The ATC200X is equipped with low pressure tubeless tires to promote comfortable riding. Although the tires are designed specifically for vigorous off-road use, they are not immune to punctures. Always select your riding area with care.

WARNING

* *The ATC is not designed to be ridden on paved surfaces. Handling and control will be severely affected.*

Check tire pressure frequently with the air pressure gauge supplied with this ATC.

For normal use, the tires should be inflated to the recommended pressure. A manually operated tire pump should be used rather than the high pressure systems found in service stations. This will minimize the possibility of tire damage from overinflation.

NOTE:

* Tire pressure should be checked when the tires are “cold,” before you ride.

If no air pressure gauge is available to accurately measure a recommended pressure, this value can be estimated by measuring the circumference of the tires with a measuring tape. When inflated to the recommended pressure, the maximum tire circumference measured over the tread ribs will be approximately standard tire circumference. The relationship between

tire pressure and actual circumference varies slightly with factors of wear and stretching that occur through use.

	Front	Rear
TIRE SIZE	23.5x8.0-11	22x10-9
TIRE BRAND	OHTSU PV101	OHTSU PV701
Recommended pressure	3.5 psi (25 kPa, 0.25 kg/cm ²)	2.5 psi (17 kPa, 0.17 kg/cm ²)
Standard tire circumference	1890 mm (74.4 in)	1720 mm (67.7 in)
Max. pressure	3.9 psi (28 kPa, 0.28 kg/cm ²)	2.9 psi (20 kPa, 0.20 kg/cm ²)
Min. pressure	3.1 psi (22 kPa, 0.22 kg/cm ²)	2.1 psi (14 kPa, 0.14 kg/cm ²)

