

## TUBELESS TYRES

This motorcycle is equipped with tubeless tyres, valves, and wheel rims. Use only tyres marked "TUBELESS" and tubeless valves on rims marked "TUBELESS TYRE APPLICABLE."

Proper air pressure will provide maximum stability, riding comfort and tyre life.

Check tyre pressure frequently and adjust if necessary.

### NOTE:

- \* Tyre pressure should be checked before you ride while the tyres are "cold".
- \* Tubeless tyres have some degree of selfsealing ability if they are punctured, and leakage is often very slow. Inspect very closely for punctures, especially if the tyre is not fully inflated.

|   |                          | Front                | Rear                 |
|---|--------------------------|----------------------|----------------------|
| Tyre size   |                          | 120/70 VR<br>17-V270 | 170/60 VR<br>17-V270 |
| Cold tyre pressures<br>kPa<br>(kg/cm <sup>2</sup> ,<br>psi) | Driver only              | 250<br>(2.50 , 36)   | 290<br>(2.90 , 42)   |
|   | Driver and one passenger | 250<br>(2.50 , 36)   | 290<br>(2.90 , 42)   |
| Tyre brand<br>TUBLESS ONLY<br>BRIDGESTONE<br>DUNLOP         |                          | CYROX19E<br>K510A    | CYROX16E<br>K510B    |