

## TUBELESS TYRES

This motorcycle is equipped with tubeless tyres, valves, and wheel rims. Use only tyres marked "TUBELESS" and tubeless valves on rims marked "TUBELESS TYRE APPLICABLE."

Proper air pressure will provide maximum stability, riding comfort and tyre life. Check tyre pressure frequently and adjust if necessary.

### NOTE:

- \* Tyre pressure should be checked before you ride while the tyres are "cold".
- \* Tubeless tyres have some degree of selfsealing ability if they are punctured, and leakage is often very slow. Inspect very closely for punctures, especially if the tyre is not fully inflated.

Tyre size	
Front	120/70 ZR17 (58W)
Rear	180/55 ZR17 (73W)
Cold tyre pressures kPa (kgf/cm <sup>2</sup> , psi)	Driver only
	Front 290 (2.90 , 42)
	Rear 290 (2.90 , 42)
	Driver and one passenger
Front 290 (2.90 , 42)	
Rear 290 (2.90 , 42)	
Tyre brand TUBELESS ONLY	DUNLOP
	Front D205F J
	Rear D205 G
	BRIDGESTONE
	Front BT57F RADIAL G
	Rear BT57R RADIAL G
MICHELIN	
Front MACADAM 90XS	
Rear MACADAM 90XS	