

## MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C : CLEAN R : REPLACE A : ADJUST L : LUBRICATE

ITEM		FREQUENCY	WHICHEVER COMES FIRST ↓ →	ODOMETER READING [NOTE (3)]							PAGE	
				EVERY	1,000 km (600 mi)	6,400 km (4,000 mi)	12,800 km (8,000 mi)	19,200 km (12,000 mi)	25,600 km (16,000 mi)	32,000 km (20,000 mi)		38,400 km (24,000 mi)
*	FUEL LINES				I	I	I	I	I	I		
*	FUEL STRAINER			C	C	C	C	C	C	C		
*	THROTTLE OPERATION			I	I	I	I	I	I	I	120	
*	CARBURETOR-CHOKE				I	I	I	I	I	I		
*	AIR CLEANER		NOTE (1)				R		R		R	118
	CRANKCASE BREATHER		NOTE (2)		C	C	C	C	C	C		126
	SPARK PLUGS				I	R	I	R	I	R		114
	ENGINE OIL		YEAR	R	R	R	R	R	R	R		108
	ENGINE OIL FILTER		YEAR	R	R	R	R	R	R	R		108
*	CARBURETOR- SYNCHRONIZATION			I	I	I	I	I	I	I		
*	CARBURETOR-IDLE SPEED			I	I	I	I	I	I	I		122