

This section tells you how to fine tune your CRF for maximum competition performance.

Initial suspension adjustments should be performed after a minimum of 2 hours of easy break-in time.

Optional front and rear suspension springs are available in both stiffer and softer than standard rates, in order to tailor your CRF specifically for your weight, riding style and course conditions.

Follow the instructions given in the rear suspension sag setting section of *Rear Suspension Adjustments* to determine if your combined rider and sprung machine weight (rider fully dressed for competition and machine coolant, oil and fuel levels ready for competition) requires an optional stiffer or softer rear spring. The need for either optional rear spring may need to be balanced by installing the optional fork springs of a similar rate.

Front Suspension Adjustments.....	112
Front Suspension Air Pressure.....	112
Front Suspension Damping	112
Fork Springs.....	113
Front Suspension Disassembly	113
Damper Oil Change	117
Fork Assembly	120
Rear Suspension Adjustments	126
Rear Suspension Spring Pre-Load	126
Rear Suspension Damping.....	127
Rear Suspension Race Sag	128
Suspension Adjustments for Track	
Conditions	130
Suspension Adjustment Guidelines.....	131
Carburetor Adjustments & Tuning Tips.....	134
Carburetor Components	134
Carburetor Removal.....	136
Carburetor Disassembly.....	137
Carburetor Assembly	139
Idle Speed Adjustment.....	140
Steering Damper Adjustment	141
Steering Damper Adjustment	141
Steering Damper Adjustment Guidelines.....	142
Chassis Adjustments.....	143
Rear End	143
Fork Height/Angle.....	143
Wheelbase.....	143
Gearing.....	144
Tire Selection for Track Conditions.....	145
Personal Fit Adjustments	146
Control Positioning.....	146
Handlebar Position, Width & Shape.....	146