

## Specifications

### Service Data

Tyre size	Front	120/70-12 51L
	Rear	130/70-12 56L
Tyre type	Bias-ply, tubeless	
Recommended Tyres	Front	VEE RUBBER V119C
	Rear	VEE RUBBER V119C
Tyre air pressure (Driver only)	Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
	Rear	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
Tyre air pressure (Driver and passenger)	Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
	Rear	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
Spark plugs	(standard)	CPR6EA-9 (NGK) or U20EPR9 (DENSO)
	(For extended high speed riding)	CPR7EA-9 (NGK) or U22EPR9 (DENSO)
Spark plug gap	0.80 to 0.90 mm (0.031 to 0.035 in)	
Idle speed	1,400 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	

Engine oil capacity	After draining	0.9 litres (1.0 US qt, 0.8 Imp qt)
	After disassembly	1.1 litres (1.2 US qt, 1.0 Imp qt)
Recommended brake fluid	Honda DOT 3 or DOT 4 Brake Fluid	