

# SPECIFICATIONS

---

## CHASSIS AND SUSPENSION

Caster	26°00'
Trail	98 mm (3.9 in)
Tyre size, front	120/70ZR18M/C (59W) BRIDGESTONE BT020F F DUNLOP D220FST L
Tyre size, rear	170/60ZR17M/C (72W) BRIDGESTONE BT020R F DUNLOP D220ST L
Tyre type	radial-ply, tubeless

## POWER TRANSMISSION

Primary reduction	1.785
Secondary reduction	0.925
Final reduction	2.833
Gear ratio, 1st	2.571
2nd	1.722
3rd	1.285
4th	1.041
5th	0.862

## ELECTRICAL

Battery	12 V—11.2 Ah
Generator	0.675 kW/5,000 min <sup>-1</sup> (rpm)

## LIGHTS

Headlight	12 V—60/55 W × 2 ..... E, ED, F type
	12 V—45/45 W × 2 ..... U type
Brake/tail light	12 V—21/5 W × 2
Turn signal light (front)	12 V—21 W × 2
(rear)	12 V—21 W × 2
Position light	12 V—5 W × 2

## FUSES

Main fuse A	30 A
Main fuse B	65 A
Other fuses	30 A, 20 A, 15 A, 10 A