

TIRES

This FOURTRAX is equipped with low pressure tubeless tires to promote comfortable riding.

Although the tires are designed specifically for vigorous off road use, they are not immune to punctures. Always select your riding area with care.

WARNING

* *The FOURTRAX is not designed to be driven on paved surfaces. Handling and control will be severely affected.*

Check the tire pressure frequently with the air pressure gauge supplied with the FOURTRAX.

For normal use, the tires should be inflated to the recommended pressure. A manually operated tire pump should be used rather than the high pressure systems found in service stations. This will minimize the possibility of tire damage from overinflation.

NOTE:

* Tire pressure should be checked when the tires are “cold,” before you ride.

		Front	Rear
TIRE SIZE		AT 23 x 8-11★★	AT 24 x 9-11★
TIRE BRAND		A/T 504 Ohtsu	A/T 502 Ohtsu
NO CARGO	RECOMMENDED PRESSURE	4.4 psi (30 kPa, 0.30 kg/cm ²)	2.9 psi (20 kPa, 0.20 kg/cm ²)
	MAX. PRESSURE	5.0 psi (34 kPa, 0.34 kg/cm ²)	3.3 psi (23 kPa, 0.23 kg/cm ²)
	MIN. PRESSURE	3.8 psi (26 kPa, 0.26 kg/cm ²)	2.5 psi (17 kPa, 0.17 kg/cm ²)
WITH CARGO	RECOMMENDED PRESSURE	5.0 psi (34 kPa, 0.34 kg/cm ²)	3.6 psi (25 kPa, 0.25 kg/cm ²)

WARNING

- * *Maintain proper tire air pressure. Improperly inflated tires may adversely affect maneuverability and may cause loss of control.*
- * *When replacing tires, use only the size, type and brand identified in the chart. The use of different sizes or types of tires can severely effect vehicle handling.*