

SPECIFICATIONS

| DIMENSIONS | |
|-------------------------------|--------------------------------------|
| Overall length | 78.1 in (1,983 mm) |
| Overall width | 45.0 in (1,143 mm) |
| Overall height | 44.1 in (1,119 mm) |
| Wheelbase | 49.3 in (1,253 mm) |
| WEIGHT | |
| Dry weight | 499.3 lbs (226.5 kg) |
| CAPACITIES | |
| Engine oil | 2.6 US qt (2.5 ℓ , 2.2 Imp qt) |
| Fuel tank | 3.43 US gal (13.0 ℓ , 2.86 Imp gal) |
| Fuel reserve | 0.85 US gal (3.2 ℓ , 0.70 Imp gal) |
| ENGINE | |
| Bore and stroke | 3.09 × 2.68 in (78.5 × 68.0 mm) |
| Compression ratio | 8.8 : 1 |
| Displacement | 20.08 cu-in (329.1 cm ³) |
| Engine idle speed | 1,400 ± 100 rpm |
| Spark plug, standard | DPR7EA-9 (NGK) X22EPR-U9 (DENSO) |
| Spark plug gap | 0.03–0.04 in (0.8–0.9 mm) |
| Valve clearance | 0.006 in (0.15 mm) |
| CHASSIS AND SUSPENSION | |
| Caster angle | 7° |
| Trail length | 1.2 in (31 mm) |
| Tire size, Front | AT24 × 8-12 ★★ |
| Rear | AT25 × 11-10 ★★ |