

## SPECIFICATIONS

<b>DIMENSIONS</b>	
Overall length	72.2 in (1,835 mm)
Overall width	45.3 in (1,150 mm)
Overall height	43.7 in (1,110 mm)
Wheelbase	48.4 in (1,230 mm)
<b>WEIGHT</b>	
Dry Weight	375 lbs (170 kg)
<b>CAPACITIES</b>	
Engine oil	2.3 US qt (2.2 ℓ , 1.9 Imp qt)
Fuel tank	2.64 US gal (10.0 ℓ , 2.20 Imp gal)
Fuel reserve	0.42 US gal (1.6 ℓ , 0.35 Imp gal)
<b>ENGINE</b>	
Bore and stroke	3.35 × 2.76 in (85.0 × 70.0 mm)
Compression ratio	9.1 : 1
Displacement	24.23 cu-in (397.2 cm <sup>3</sup> )
Engine idle speed	1,400 ± 100 rpm
Spark plug, standard	DPR8Z (NGK) X24GPR-U (DENSO)
Spark plug gap	0.024–0.028 in (0.60–0.70 mm)
Valve clearance Intake	0.004 in (0.10 mm)
Exhaust	0.005 in (0.12 mm)
<b>CHASSIS AND SUSPENSION</b>	
Caster angle	6.5°
Trail length	1.1 in (28 mm)
Tire size, Front	AT 22 × 7-10 ★★
Rear	AT 20 × 10-9 ★★