

|            |                      | FRONT  | REAR   |
|------------|----------------------|--|--|
| TIRE SIZE  |                      | AT25 × 8-12 ★★                               | AT25 × 10-12 ★★                              |
| TIRE BRAND |                      | KT401C DUNLOP                                | KT405C DUNLOP                                |
| NO CARGO   | RECOMMENDED PRESSURE | 3.6 psi (25 kPa , 0.25 kgf/cm <sup>2</sup> ) | 3.6 psi (25 kPa , 0.25 kgf/cm <sup>2</sup> ) |
|            | MAXIMUM PRESSURE     | 4.0 psi (28 kPa , 0.28 kgf/cm <sup>2</sup> ) | 4.0 psi (28 kPa , 0.28 kgf/cm <sup>2</sup> ) |
|            | MINIMUM PRESSURE     | 3.2 psi (22 kPa , 0.22 kgf/cm <sup>2</sup> ) | 3.2 psi (22 kPa , 0.22 kgf/cm <sup>2</sup> ) |
| WITH CARGO | RECOMMENDED PRESSURE | 3.6 psi (25 kPa , 0.25 kgf/cm <sup>2</sup> ) | 3.6 psi (25 kPa , 0.25 kgf/cm <sup>2</sup> ) |

Fig. 4-35

Tire specifications

## **▲ WARNING**

### **POTENTIAL HAZARD**

**Operating this ATV with improper tires, or with uneven tire pressure.**

### **WHAT CAN HAPPEN**

**Use of improper tires on this ATV, or operation of this ATV with improper or uneven tire pressure, may cause loss of control, increasing your risk of an accident.**

### **HOW TO AVOID THE HAZARD**

**Always use the size and type tires specified in this Owner's Manual for this vehicle.**

**Always maintain proper tire pressure as described in this Owner's Manual.**