

# Specifications

| <b>Electrical</b> |                    |
|-------------------|--------------------|
| battery           | 12 V – 12 Ah       |
| generator         | 0.361 kW/5,000 rpm |

| <b>Lights</b>                          |                  |
|--|------------------|
| headlight                              | 12 V 30/30 W × 2 |
| assist headlight                       | 12 V 45 W        |
| brake/tail light                       | 12 V 21/5 W × 2  |
| neutral indicator                      | LED              |
| reverse indicator                      | LED              |
| high oil/coolant temperature indicator | LED              |
| 4WD indicator                          | LED              |

| <b>Fuses</b>     |                    |
|------------------|--------------------|
| main             | 30 A               |
| shift motor fuse | 30 A               |
| other            | 15 A × 2, 10 A × 2 |

| <b>Torque Specification</b>         |                                |
|-------------------------------------|--------------------------------|
| oil tank drain bolt                 | 18 lbf·ft (25 N·m , 2.5 kgf·m) |
| crankcase drain bolt                | 18 lbf·ft (25 N·m , 2.5 kgf·m) |
| oil filter bolt                     | 13 lbf·ft (18 N·m , 1.8 kgf·m) |
| rear final gear case oil drain bolt | 9 lbf·ft (12 N·m , 1.2 kgf·m)  |
| differential oil drain bolt         | 9 lbf·ft (12 N·m , 1.2 kgf·m)  |
| wheel nuts                          | 47 lbf·ft (64 N·m , 6.5 kgf·m) |