

Specifications

Service Data

Tyre size	Front	120/70ZR17M/C(58W)
	Rear	180/55ZR17M/C(73W)
Tyre type	Radial, tubeless	
Recommended Tyres	Front	DUNLOP D222F K BRIDGESTONE T30F G
	Rear	DUNLOP D222 K BRIDGESTONE T30R G
Tyre air pressure	Front	250 kPa (2.50 kgf/cm ² , 36 psi)
	Rear	290 kPa (2.90 kgf/cm ² , 42 psi)
Minimum tread depth	Front	1.5 mm (0.06 in)
	Rear	2.0 mm (0.08 in)
Spark plugs	(standard) IMR9D-9H (NGK) or VNIH27ZB (DENSO)	
Spark plug gap	(non-adjustable) 0.80 to 0.90 mm (0.031 to 0.035 in)	
Idle speed	(non-adjustable) 1,200 ± 100 rpm	
Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MA	

Engine oil capacity	After draining	2.9 litres (3.1 US qt, 2.6 Imp qt)
	After draining & engine oil filter change	3.1 litres (3.3 US qt, 2.7 Imp qt)
	After disassembly	3.9 litres (4.1 US qt, 3.4 Imp qt)
Recommended brake (clutch) fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	2.92 litres (3.09 US qt, 2.57 Imp qt)	
Recommended coolant	Pro Honda HP Coolant	