

Specifications

Recommended drive chain lubricant	Drive chain lubricant designed specifically for O-ring chains. If not available, use SAE 80 or 90 gear oil.	
Drive chain slack	30 to 40 mm (1.2 to 1.6 in)	
Standard drive chain	DID 525HV3 or RK 525ROZ6	
	No. of links	110
Standard sprocket sizes	Engine sprocket	16T
	Rear wheel sprocket	43T

■ Bulbs

Headlight	LED
Brakelight	LED
Tail light	LED
Front turn signal lights	LED
Rear turn signal lights	LED
License plate light	12V-5W

■ Fuses

Main fuse	30A
Other fuses	30A, 20A, 10A

■ Torque Specifications

Engine oil drain bolt	30 N·m (3.1 kgf·m, 22 lbf·ft)
Oil filter	26 N·m (2.7 kgf·m, 19 lbf·ft)
Bearing holder pinch bolt	74 N·m (7.5 kgf·m, 55 lbf·ft)
Seat adjust plate socket bolts A	22 N·m (2.2 kgf·m, 16 lbf·ft)
Seat adjust set collar socket bolts B/socket bolt C	12 N·m (1.2 kgf·m, 9 lbf·ft)
Front wheel axle bolt	59 N·m (6.0 kgf·m, 44 lbf·ft)
Front wheel brake caliper mounting bolts	45 N·m (4.6 kgf·m, 33 lbf·ft)
Front wheel axle pinch bolts	22 N·m (2.2 kgf·m, 16 lbf·ft)
Rear wheel nuts	108 N·m (11.0 kgf·m, 80 lbf·ft)
Muffler mounting nut	27 N·m (2.8 kgf·m, 20 lbf·ft)
Muffler band bolts	21 N·m (2.1 kgf·m, 15 lbf·ft)