

TIRE RECOMMENDATION

- Off-the-road “knobbs-type” tires are standard on this model. Select the right tires in accordance with the following specifications :

Tire Brand	Bridge-stone	Front: TRAIL WING 5A Rear: TRAIL WING 5A
	Nitto	Front: NT-102B Rear: NT-102B
Tire size		Front: 3.00-21 Rear: 4.00-18
Tire air pressure (cold)		Front: 21 psi (1.5 kg/cm ²) Rear: 21 psi (1.5 kg/cm ²)
Vehicle capacity load		220 lbs (100 kg) operator only

When riding at any speed higher than **60 mph**, use the tires specified below :

Tire Brand	Bridge-stone	Front: TRAIL WING Rear: TRAIL WING
	Nitto	Front: NT-116 Rear: NT-116

- Over inflation or under inflation of the tires causes abnormal tread wear or other defects which may result in serious accidents. Riding with underinflated tires causes the tires to slip or the rims, damaging the innertubes. When riding with low air pressure (below **14 psi (1 kg/cm²)**, be sure to install rim locks on the rear wheel.
- From time to time check tire air pressure and adjust if necessary.
- Replace the tires when the center block height of the tread is less than **0.12 in. (3 mm)**.
- Adjust tire pressures when tires are cad.