

## MAINTENANCE

---

Front brake lever free play	15–20 mm (5/8–3/4 in)
Rear brake pedal free play	15–20 mm (5/8–3/4 in)
Rear brake lever (parking brake) lever free play	15–20 mm (5/8–3/4 in)
Drive chain free play	10–20 mm (3/8–3/4 in)
Drive chain length (45 pins):	
Standard	698.5 mm (27.50 in)
Service limit	705.5 mm (27.78 in)
Front/rear rim size	9.2 x 9.0
Front/rear tire size	25 x 12–9
Front/rear tire pressure	2.2 psi (0.15 kg/cm <sup>2</sup> , 15 kPa)
Front/rear tire circumference	
Standard	1,870 mm (73.6 in)

## TORQUE VALUES

Spark plug	12–19 N·m (1.2–1.9 kg-m, 9–14 ft-lb)
Valve adjuster cover	10–14 N·m (1.0–1.4 kg-m, 7–10 ft-lb)
Cam chain tensioner adjusting bolt	15–22 N·m (1.5–2.2 kg-m, 11–16 ft-lb)
Rear axle bearing holder bolt	50–70 N·m (5.0–7.0 kg-m, 36–51 ft-lb)
Clutch adjuster lock nut	19–25 N·m (1.9–2.5 kg-m, 14–18 ft-lb)
Valve adjuster lock nut	15–18 N·m (1.5–1.8 kg-m, 11–13 ft-lb)