

## 5. FRONT WHEEL/SUSPENSION/STEERING

### SERVICE INFORMATION

#### SPECIFICATIONS

	SERVICE LIMIT
Front fork spring A	122.6 mm (4.8 in)
B	452.9 mm (17.8 in)
Front fork oil capacity	281 cc (9.5 oz)
Front fork oil level	177 mm (7.0 in)

#### TORQUE VALUES

Front axle	70–110 N·m (7.0–11.0 kg-m, 51–80 ft-lb)
Axle holder nut	10–14 N·m (1.0–1.4 kg-m, 7–10 ft-lb)
Front hub nut	30–40 N·m (3.0–4.0 kg-m, 22–29 ft-lb)
Steering stem adjuster nut	See page 18-29
Steering stem nut	80–120 N·m (8.0–12.0 kg-m, 58–87 ft-lb)
Front fork upper pinch bolts	18–25 N·m (1.8–2.5 kg-m, 13–18 ft-lb)
Front fork lower pinch bolts	18–25 N·m (1.8–2.5 kg-m, 13–18 ft-lb)

#### TOOLS

##### SPECIAL

DESCRIPTION	TOOL NUMBER	REMARKS
Universal bead breaker	GN-AH-958-BB1	U.S.A. only
Fork seal driver	07947-3290000	
Steering race remover	07953-4250002	
Steering stem socket	07916-3710100	
Steering stem driver	07946-3710600 or 07946-3710601	
Attachment	GN-HT-54	U.S.A. only
Driver	07945-3710300	

##### COMMON

DESCRIPTION	TOOL NUMBER	REMARKS
Attachment, 42 x 47 mm	07746-0010300	
Pilot, 15 mm	07746-0040300	
Driver	07749-0010000	