





Items		Frequency	Odometer Reading*1							Refer to page		
			× 1,000 mi	0.6	4	8	12	16	20		24	
			× 1,000 km	1.0	6.4	12.8	19.2	25.6	32.0		38.4	
Non-Emission-Related Items	Drive Chain	Every 500 mi (800 km)	I	L							70	
	Drive Chain Slider			I	I	I	I	I	I		73	
	Brake Fluid*5			I	I	R	I	I	R		66	
	Brake Pads Wear			I	I	I	I	I	I		67	
	Brake System		I		I		I		I		66	
	Brake Light Switch				I		I		I		79	
	Headlight Aim				I		I		I		79	
	Clutch System				I		I		I		76	
	Clutch Fluid*5			I	I	R	I	I	R		68	
	Side Stand				I		I		I		69	
	Suspension					I		I		I		77
	Nuts, Bolts, Fasteners			I		I		I		I		-
	Wheels/Tires					I		I		I		49
Steering Head Bearings			I		I		I		I		-	

Maintenance Legend

- I** : Inspect (clean, adjust, lubricate, or replace, if necessary)
- C** : Clean
- L** : Lubricate
- R** : Replace

Notes:

- *1 : At higher odometer readings, repeat at the frequency interval established here.
- *2 : Service more frequently when riding in unusually wet or dusty areas.
- *3 : Service more frequently when riding in rain or at full throttle.
- *4 : 50 STATE type (meets California)
- *5 : Replace every 2 years, or at indicated odometer intervals, whichever comes first. Replacement requires mechanical skill.