

Recommended drive chain lubricant	Pro Honda HP Chain Lube	
Drive chain slack	1.0 to 1.4 in (25 to 35 mm)	
Standard drive chain	DID50ZVM2 or RK50LF0Z2	
	No. of links	110
Standard sprocket sizes	Engine sprocket	18T
	Rear wheel sprocket	39T

### ■ Bulbs

Headlight	12V-60/55W	
Brake/Tail light	12V-21/5W	
Front turn signal lights	12V-21W x 2	
Rear turn signal lights	12V-21W x 2	

### ■ Fuses

Main fuse	30A	
Other fuses	<b>CB1100</b>	20A, 10A
	<b>CB1100A</b>	30A, 20A, 10A

### ■ Torque Specifications

Engine oil drain bolt	22 lbf·ft (30 N·m, 3.1 kgf·m)
Oil filter	19 lbf·ft (26 N·m, 2.7 kgf·m)
Front wheel axle bolt	43 lbf·ft (59 N·m, 6.0 kgf·m)
Front wheel brake caliper mounting bolts	23 lbf·ft (31 N·m, 3.2 kgf·m)
Front wheel axle pinch bolts	19 lbf·ft (26 N·m, 2.7 kgf·m)
Rear wheel axle nut	83 lbf·ft (113 N·m, 11.5 kgf·m)