







Items		Frequency	Odometer Reading*1							Refer to page	
			× 1,000 mi	0.6	4	8	12	16	20		24
			× 1,000 km	1.0	6.4	12.8	19.2	25.6	32.0		38.4
Non-Emission-Related Items	Drive chain		Every 500 mi (800 km): I L							72	
	Brake Fluid*4			I	I	R	I	I	R	68	
	Brake Pads Wear			I	I	I	I	I	I	69	
	Brake System		I		I		I		I	68	
	Brake Light Switch				I		I		I	-	
	Headlight Aim				I		I		I	-	
	Clutch System				I		I		I	77	
	Clutch Fluid*4			I	I	R	I	I	R	75	
	Side Stand				I		I		I	71	
	Suspension				I		I		I	78	
	Nuts, Bolts, Fasteners			I		I		I		I	-
	Wheels/Tires					I		I		I	50
Steering Head Bearings			I		I		I		I	-	

Maintenance Legend

I : Inspect (clean, adjust, lubricate, or replace, if necessary)

C : Clean **R** : Replace **L** : Lubricate

Notes:

*1 : At higher odometer readings, repeat at the frequency interval established here.

*2 : Service more frequently when riding in unusually wet or dusty areas.

*3 : Service more frequently when riding in rain or at full throttle.

*4 : Replace every 2 years, or at indicated odometer intervals, whichever comes first. Replacement requires mechanical skill.