

Specifications

■ Main Components

Type	SC59
Overall length	81.7 in (2,075 mm)
Overall width	27.0 in (685 mm)
Overall height	44.7 in (1,135 mm)
Wheelbase	55.5 in (1,410 mm)
Minimum ground clearance	5.1 in (130 mm)
Caster angle	23° 30'
Trail	3.8 in (96 mm)
Curb weight	CBR1000RR
	Except California 441 lb (200 kg)
	California only 443 lb (201 kg)
	CBR1000RR ABS
Except California 465 lb (211 kg)	
California only 467 lb (212 kg)	
Maximum weight capacity*1	366 lb (166 kg)
Maximum luggage weight*2	66 lb (30 kg)
	Luggage 31 lb (14 kg)
	Accessories 35 lb (16 kg)
Passenger capacity	Rider and 1 passenger
Minimum turning radius	9.9 ft (3 m)

*1 Including rider, passenger, all luggage, and accessories

*2 Includes the weight of the luggage and added accessories.

Displacement	60.9 cu-in (999 cm ³)
Bore x stroke	2.99 x 2.17 in (76.0 x 55.1 mm)
Compression ratio	12.3:1
Fuel	Unleaded gasoline Recommended: 91 PON or higher
Tank capacity	4.68 US gal (17.7 liters)
Battery	CBR1000RR
	YTZ7S 12V-6Ah (10 HR)
	CBR1000RR ABS
	YTZ10S 12V-8.6Ah (10 HR)
Gear ratios	1st 2.285
	2nd 1.777
	3rd 1.500
	4th 1.333
	5th 1.214
	6th 1.137
Reduction ratios (primary / final)	1.717 / 2.625