## **Specifications**

■ Main Components

I Main Components				
Туре		SC59		
Overall length		81.7 in (2,075 mm)		
Overall width		27.0 in (685 mm)		
Overall height		44.7 in (1,135 mm)		
Wheelbase		55.5 in (1,410 mm)		
Minimum ground clearance		5.1 in (130 mm)		
Caster angle		23° 30′		
Trail		3.8 in (96 mm)		
		49 STATE	441 lb (200 kg)	
	CBR1000RR	50 STATE (meets California)		
Curb weight			443 lb (201 kg)	
	CBR1000RR ABS	50 STATE (meets California)		
			467 lb (212 kg)	
		Canada model	465 lb (211 kg)	
Maximum capacity*1	weight	366 lb (166 kg)		
	luggage	66 lb (30 kg)		
weight*2		Luggage	31 lb (14 kg)	
weight -		Accessories	35 lb (16 kg)	
Passenger capacity		Rider and 1 passenger		
Minimum turning radius		9.9 ft (3 m)		
		· ·		

<sup>\*1</sup> Including rider, passenger, all luggage, and accessories \*2 Includes the weight of the luggage and added accessories.

Displacement	60.9 cu-in (999 cm³)		
Bore x stroke	2.99 × 2.17 in (76.0 x 55.1 mm)		
Compression ratio	12.3:1		
Fuel	Unleaded gasoline Recommended: 91 PON or higher		
Tank capacity	4.68 US gal (17.7 liters)		
	CBR1000RR		
Pattoni	YTZ7S 12V-6Ah (10 HR)		
Battery	CBR1000RR ABS		
	YTZ10S 12V-8.6Ah (10 HR)		
	1st	2.285	
	2nd	1.777	
Gear ratios	3rd	1.500	
deal fatios	4th	1.333	
	5th	1.214	
	6th	1.137	
Reduction ratios (primary / final)		1.717 / 2.625	