

# Specifications

## ■ Main Components

Overall length	2,060.5 mm (81.12 in)
Overall width	724 mm (28.5 in)
Overall height	1,098 mm (43.2 in)
Wheelbase	1,389 mm (54.7 in)
Minimum ground clearance	145 mm (5.7 in)
Caster angle	24° 30'
Trail	92.3 mm (3.63 in)
Curb weight	169 kg (373 lb)
Maximum weight capacity *1	160 kg (353 lb)
Passenger capacity	Rider and 1 passenger
Minimum turning radius	2.9 m (9.5 ft)

\*1 : Including rider, passenger, all luggage, and accessories.

Displacement	249.74 cm <sup>3</sup> (15.234 cu-in)	
Bore x stroke	62.000 x 41.360 mm (2.4409 x 1.6283 in)	
Compression ratio	12.1:1	
Fuel	Unleaded petrol Recommended: 91 RON or higher	
Fuel containing alcohol	ETHANOL up to 10 % by volume	
Tank capacity	14.5 L (3.83 US gal, 3.19 Imp gal)	
Battery	GTZ8V 12 V-7 Ah (10 HR)	
Gear ratio	1st	3.181
	2nd	2.187
	3rd	1.727
	4th	1.421
	5th	1.222
	6th	1.068
Reduction ratio (primary / final)	2.781 / 2.928	