Quick Reference

The following is a brief, but important collection of information you need to know about your Honda. You'll also find space to record important notes.

How To Avoid Costly Repairs

The engine of your Honda can be the most expensive component to repair. Proper maintenance, especially the use of the recommended fluids and filters, prevents premature wear and damage.

Frequent causes of costly engine repairs are:

- Transmission oil & engine oil: insufficient quantity, improper oil.
- Air cleaner: dirty, leaking because of improper installation (poor seal).

Record important information here:

| VIN | |
|--------------|--|
| Engine No. | |
| Owner's: | |
| Name | |
| Address | |
| City/State | |
| Phone | |
| Dealer's: | |
| Name | |
| Address | |
| City/State | |
| Phone | |
| Service Mgr. | |

| Maintenance | The maintenance schedule (page 21) lists service frequencies for: each race or about 2.5 hours, every 3 races or about 7.5 hours, and every 6 races or about 15.0 hours every 9 races or about 22.5 hours | | | | | | | | | | |
|----------------------|---|-----------|----------------|-------------|-------|---------------|----|-------------|------|--|--|
| Pre-ride Inspection | Check the items listed on the Pre-ride inspection checklist each time before you ride (page 9): | | | | | | | | | | |
| Fuel/Capacity | unleaded gasoline, pump octane number of 91 or higher tank: 1.14 US gal (4.3 ℓ) | | | | | | | | | | |
| Engine oil | Pro Honda GN4 4-stroke oil, or an equivalent. | | | | | | | | | | |
| Transmission oil | Pro Honda GN4 4-stroke oil, or an equivalent. | | | | | | | | | | |
| Tires | CRF150R | Front | 70/100–17 40M | | | 90/100-14 49M | | | | | |
| 11100 | | | AC | DUNLOP | MX71F | Rear | AC | DUNLOP | MX71 | | |
| | | | СМ | BRIDGESTONE | M23 | | СМ | BRIDGESTONE | M22 | | |
| | CRF150RB | Front | 70/100–19 42M | | | 90/100-16 52M | | | | | |
| | | | AC | DUNLOP | MX71F | Rear | AC | DUNLOP | MX71 | | |
| | | | СМ | BRIDGESTONE | M61 | | СМ | BRIDGESTONE | M58 | | |
| | Туре | | bias-ply, tube | | | | | | | | |
| Tire Pressure (cold) | Front: 15 psi (100 kPa, 1.0kgf/cm²) Rear: 15 psi (100 kPa, 1.0kgf/cm²) | | | | | | | | | | |
| Spark Plug | Standard: CR8EH-9 (NGK), U24FER9 (DENSO) Optional: CR9EH-9 (NGK), U27FER9 (DENSO) | | | | | | | | | | |
| Coolant | ethylene glycol antifreeze (silicate-free) for aluminum engines in 50/50 solution with Pro Honda HP Coolant or equivalent distilled water. | | | | | | | | | | |
| Drive Chain | DID420DS3 | DID420DS3 | | | | | | | | | |