

Specifications

Recommended final drive oil	Hypoid gear oil SAE 80	
Final drive oil capacity	After draining	4.7 US oz (140 cm ³)
	After disassembly	5.4 US oz (160 cm ³)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	3.06 US qt (2.90 liters)	
Recommended coolant	Pro Honda HP Coolant	

■ Bulbs

Headlight	LED
Brake light	LED
Taillight	LED
Front turn signal light	LED
Rear turn signal light	LED
License plate light	LED

■ Fuses

Ignition main fuse	30 A
ACC main fuse	20 A
Main fuse B	120 A
External amplifier fuse	40 A
Other fuse	30 A, 15 A, 10 A, 5 A

■ Torque Specifications

Oil filter	19 lbf-ft (26 N-m, 2.7 kgf-m)
Engine oil drain bolt A	22 lbf-ft (30 N-m, 3.1 kgf-m)
Engine oil drain bolt B	22 lbf-ft (30 N-m, 3.1 kgf-m)
Engine oil drain bolt C	22 lbf-ft (30 N-m, 3.1 kgf-m)
Final drive oil fill hole cap	5.9 lbf-ft (8 N-m, 0.8 kgf-m)
Final drive oil drain bolt	9 lbf-ft (12 N-m, 1.2 kgf-m)
Front wheel axle bolt	44 lbf-ft (59 N-m, 6.0 kgf-m)
Front wheel axle pinch bolt	16 lbf-ft (22 N-m, 2.2 kgf-m)
Front wheel brake caliper mounting bolt	31 lbf-ft (42.5 N-m, 4.3 kgf-m)
Rear wheel nut	80 lbf-ft (108 N-m, 11.0 kgf-m)