

Specifications

Service Data

Tyre size (Dunlop)	Front	80/100-21 M/C 51 M
	Rear	120/100 R18 M/C 68 M
Tyre size (Michelin)	Front	2,75-21 M/C 45 L 2,75-21 M/C 45 M *2
	Rear	4.00 R18 M/C 64L 4.00 R18 M/C 64M *2
Tyre type	Front	Inner tube
	Rear	Tubeless
Recommended tyres (Dunlop)	Front	D803FGP
	Rear	D803GP
Recommended tyres (Michelin)	Front	TRIAL COMPETITION
	Rear	TRIAL COMPETITION X11
Tyre pressure (road)	Front	100 kPa (1,02 kgf/cm ²)
	Rear	100 kPa (1,02 kgf/cm ²)
Tyre pressure (off road)	Front	70 kPa (0,7 kgf/cm ²)
	Rear	60 kPa (0,6 kgf/cm ²)
Minimum tread depth	Front	3.0 mm (0.12 in)
	Rear	3.0 mm (0.12 in)
Spark Plug	(standard)	CR6EH-9 (NGK)

*2 Minimum speed rating "L"

Spark plug gap	(not adjustable)	0,80 a 0,90 mm
Idle Speed:	1800 ± 100 r.p.m.	
Recommended engine oil	Motorcycle oil - 4-stroke Repsol 4T SAE 10W30 or equivalent	
Specified transmission oil	REPSOL MOTO TRANSMISSION (75W) ELF HTX740 (75W)	
Engine oil capacity	After draining	0.41 litres (0.86 US gal, 0.72 Imp. gal)
	After draining and filter replacement	0.44 litres (0.93 US gal, 0.77 Imp. gal)
	After disassembly	0.60 litres (1.26 US gal, 1.05 Imp. gal)
Transmission oil capacity	After draining	0.54 litres (1.14 US gal, 0.95 Imp. gal)
	After disassembly	0.57 litres (1.20 US gal, 1.00 Imp. gal)
Recommended brake and clutch fluid	DOT 4	
Cooling system capacity	After draining	0.50 litres (1.06 US gal, 0.87 Imp. gal)
	After disassembly	0.59 litres (1.25 US gal, 1.04 Imp. gal)
Recommended coolant	50 / 50 Mixture of coolant and distilled water	

Specifications