

| | | |
|-----------------------------------|---------------------------------------|-----|
| Recommended drive chain lubricant | Pro Honda HP Chain Lube or equivalent | |
| Drive chain slack | 1 3/16 to 1 9/16 in (30 to 40 mm) | |
| Standard drive chain | DID 420D | |
| | No. of links | 106 |
| Standard sprocket sizes | Engine sprocket | 15T |
| | Rear wheel sprocket | 34T |

■ Bulbs

| | |
|--------------------------|---------------|
| Headlight | 12V-35/35W |
| Brake/Tail light | LED |
| Front turn signal lights | 12V-21/5W x 2 |
| Rear turn signal lights | 12V-21W x 2 |
| License plate lights | 12V-5W |

■ Fuses

| | |
|-------------|-----|
| Main fuse | 15A |
| Other fuses | 10A |

■ Torque Specifications

| | |
|------------------------------|---------------------------------|
| Engine oil drain bolt | 18 lbf-ft (24 N·m, 2.4 kgf·m) |
| Air cleaner element screw | 0.8 lbf-ft (1.1 N·m, 0.1 kgf·m) |
| Air cleaner case cover screw | 0.8 lbf-ft (1.1 N·m, 0.1 kgf·m) |
| Rear axle nut | 44 lbf-ft (59 N·m, 6.0 kgf·m) |
| Front axle nut | 40 lbf-ft (54 N·m, 5.5 kgf·m) |