Specifications

■ Main Components

= main components			
Overall length		93.7 in (2,380 mm)	
Overall width		31.9 in (810 mm)	
Overall height		46.1 in (1,170 mm)	
Wheelbase		64.8 in (1,645 mm)	
Minimum ground clearance		5.1 in (130 mm)	
Caster angle		33° 00′	
Trail		4.3 in (110 mm)	
Curb weight		562 lb (255 kg)	
Maximum weight capacity *1		346 lb (157 kg)	
Maximum luggage weight *2	Front utility	Right 4.5 lb ((2.0 kg)
	box	Left 4.5 lb ((2.0 kg)
	Rear utility box	Right 6.6 lb ((3.0 kg)
		Left 6.6 lb ((3.0 kg)
Passenger capacity		Rider and 1 passenger	
Minimum turning radius		10.2 ft (3.1 m)	
Displacement		40.9 cu-in (670 cm ³)	
Bore x stroke		2.87 x 3.15 in (73.0 x 80.0 mm)	
Compression ratio		10.7 : 1	
Fuel	Unleaded gasoline		
ruei	Recommended: 86 PON or higher		higher
Tank capacity		3.06 US gal (11.6 L)	
Battery YTZ12S		12 V-11.0 Ah (10 HR)	

Gear ratio	1st	2.666
	2nd	1.904
	3rd	1.454
	4th	1.200
	5th	1.033
	6th	0.837
Reduction ratio (primary / final)		1.921 / 2.437
		-

^{*1:} Including rider, passenger, all luggage, and accessories *2: Includes the weight of the luggage and added accessories