Specifications

	NC700X/750XA	Recommended		
Engine oil capacity	After draining 3.3 US qt (3.1 liters)	drive chain	Pro Honda HP Chain lube or equ	ivalent
	After draining & engine oil filter 3.6 US qt (3.4 liters) change		1 3/16 to 1 9/16 in (30 to 40 mm) DID 520V0 or RK 520KHO	
	After 3.9 US qt (3.7 liters)	Standard drive chain	NC700X/750XA No. of links	114
	NC700XD/750XD		NC700XD/750XD	
	After draining 3.4 US qt (3.2 liters)		No. of links	112
	After draining & engine oil filter 3.6 US qt (3.4 liters) change	Standard sprocket sizes	NC700X/XD Engine sprocket NC750XA/XD	16T
	After draining, engine & clutch 3.6 US qt (3.4 liters) oil filter change		Engine sprocket NC700X/750XA	17T
	After 4.3 US qt (4.1 liters)		Rear wheel sprocket NC700XD/750XD	43T
Recommended brake fluid	Honda DOT 4 Brake Fluid		Rear wheel sprocket	39T
Cooling system	1.79 US qt (1.69 liters)	Bulbs	42) / 60/55) 1/	
capacity	1.75 05 qt (1.05 itters)	Headlight	12V-60/55W	
Recommended	Pro Honda HP Coolant	Brake/Tail light	LED	
coolant		Front turn signal		
		Rear turn signal	lights 12V-21W x 2	

License plate light

12V-5W