

Specifications

■ Bulbs

Headlight	12V-60/55W
Brake/Taillight	LED
Front turn signal lights	12V-21/5W x 2
Rear turn signal lights	12V-21W x 2
License plate light	12V-5W

■ Fuses

Main fuse	30A
Other fuses	VT1300CX 20A, 10A
	VT1300CXA 30A, 20A, 10A

■ Torque Specifications

Engine oil drain bolt	22 lbf-ft (30 N-m, 3.1 kgf-m)
Oil filter	19 lbf-ft (26 N-m, 2.7 kgf-m)
Final drive oil fill hole cap	9 lbf-ft (12 N-m, 1.2 kgf-m)
Final drive oil drain bolt	9 lbf-ft (12 N-m, 1.2 kgf-m)
Air cleaner housing cover bolts	1.1 lbf-ft (1.5 N-m, 0.2 kgf-m)
Front wheel axle bolt	47 lbf-ft (64 N-m, 6.5 kgf-m)
Front wheel axle pinch bolts	16 lbf-ft (22 N-m, 2.2 kgf-m)
Front wheel caliper fixing bolts	23 lbf-ft (31 N-m, 3.2 kgf-m)
Rear wheel axle nut	94 lbf-ft (127 N-m, 13.0 kgf-m)
Rear wheel axle holding bolt	20 lbf-ft (27 N-m, 2.8 kgf-m)
Rear brake bracket bolt	51 lbf-ft (69 N-m, 7.0 kgf-m)
Exhaust pipe joint nuts	17 lbf-ft (23 N-m, 2.3 kgf-m)
Muffler bracket bolt A, B, and nuts	20 lbf-ft (27 N-m, 2.8 kgf-m)