

## Specifications

### ■ Service Data

Tire size	Front	120/90-17M/C 64S
	Rear	160/80-15M/C 74S
Tire type	bias-ply, tube	
Recommended tire	Front	DUNLOP D404 FG
		BRIDGESTONE G701 CHENG SHIN M6002
	Rear	DUNLOP D404
		BRIDGESTONE G702 CHENG SHIN M6011R
Tire air pressure	Front	29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> )
	Rear	29 psi (200 kPa, 2.00 kgf/cm <sup>2</sup> ) *1 36 psi (250 kPa, 2.50 kgf/cm <sup>2</sup> ) *2
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plug	(standard)	DPR7EA-9 (NGK) or X22EPR-U9 (DENSO)
	(high speed riding)	DPR8EA-9 (NGK) or X24EPR-U9 (DENSO)
Spark plug gap	(non-adjustable)	0.031 - 0.035 in (0.80 - 0.90 mm)
Idle speed	1,200 ± 100 rpm	

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
Engine oil capacity	After draining	2.6 US qt (2.5 L)
	After draining & filter change	2.7 US qt (2.6 L)
	After disassembly	3.4 US qt (3.2 L)
Recommended final drive oil	Hypoid gear oil SAE 80	
Final drive oil capacity	After draining	5.4 US oz (160 cm <sup>3</sup> )
	After disassembly	5.7 US oz (170 cm <sup>3</sup> )
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	2.07 US qt (1.96 L)	
Recommended coolant	Pro Honda HP Coolant	

\*1: With less than 200 lb (90 kg) of added weight.

\*2: With more than 200 lb (90 kg) of added weight.