

## Specifications

### ■ Torque Specifications

Engine oil drain bolt	21 lbf-ft (29 N·m, 3.0 kgf·m)
Oil filter	19 lbf-ft (26 N·m, 2.7 kgf·m)
Final drive oil fill hole cap	9 lbf-ft (12 N·m, 1.2 kgf·m)
Final drive oil drain bolt	9 lbf-ft (12 N·m, 1.2 kgf·m)
Front wheel axle bolt	44 lbf-ft (59 N·m, 6.0 kgf·m)
Front wheel axle pinch bolts	16 lbf-ft (22 N·m, 2.2 kgf·m)
<b>(VT750C2/C2F/C2B)</b>	
Rear brake stopper arm nut	16 lbf-ft (22 N·m, 2.2 kgf·m)
<b>(VT750C2S)</b>	
Rear brake bracket bolt	51 lbf-ft (69 N·m, 7.0 kgf·m)
Rear wheel axle nut	65 lbf-ft (88 N·m, 9.0 kgf·m)
Rear wheel axle holding bolt	20 lbf-ft (27 N·m, 2.8 kgf·m)
Exhaust pipe joint nuts	18 lbf-ft (25 N·m, 2.5 kgf·m)
Muffler bracket nut	20 lbf-ft (27 N·m, 2.8 kgf·m)
Footpeg bolt A, B and nut	29 lbf-ft (39 N·m, 4.0 kgf·m)