

## b. Specifications CB 750

	Item	English	Metric
DIMENSION	Overall Length	85.0 in.	2,160 mm
	Overall Width	34.8 in.	885 mm
	Overall Height	45.5 in.	1,155 mm
	Wheel Base	57.3 in.	1,455 mm
	Seat Height	31.5 in.	800 mm
	Foot Peg Height	12.2 in.	310 mm
	Ground Clearance	5.5 in.	160 mm
	Curb Weight	517.3 lb.	235 kg
	Weight Distribution L/R	271.1/209.5 lb.	123/205 kg
FRAME	Type	Double cradle tubular steel	
	F. Suspension, Travel	Telescopic fork, travel 5.6 in. 143 mm	
	R. Suspension, Travel	Swing arm, travel 3.3 in. 85 mm	
	F. Tire Size, Type	3.25-19 (4 PR) Rib tire, tire air pressure 2.0 kg/cm <sup>2</sup> , 28 psi	
	R. Tire Size, Type	4.00-18 (4 PR) Block tire, tire air pressure 2.0 kg/cm <sup>2</sup> , 28 psi	
	F. Brake, Lining Area	Disc brake, lining area 2.9 in <sup>2</sup> × 2, 19 cm <sup>2</sup> × 2	
	R. Brake, Lining Area	Internal expanding shoe, lining area 8.2 in <sup>2</sup> × 2, 53 cm <sup>2</sup> × 2	
	Fuel Capacity	4.7 U.S. gal. 3.9 Imp. gal.	18 lit.
	Fuel Reserve Capacity	1.3 U.S. gal. 1.1 Imp. gal.	5 lit.
	Caster Angle	63°	
	Trail Length	3.74 in.	95 mm
	Front Fork Oil Capacity	7.0-7.3 ozs	220-230 cc
	ENGINE	Type	Air-cooled, 4-stroke, O.H.C. engine
Cylinder Arrangement		4-cylinder in line	
Bore and Stroke		2.401 × 2.408 in.	61 × 63 mm
Displacement		44.93 cu in.	736 cc
Compression Ratio		9.0	
Carburetor, Venturi Dia		Four, piston valve, 28 mm dia.	
Valve Train		Chain drive overhead camshaft	
Maximum Horsepower		67 BHP/8,000 rpm	
Maximum Torque		44.12 lb-ft/7,000 rpm	6.1 kg-m/7,000 rpm
Oil Capacity		7.39 U.S. pt., 6.16 Imp. pt.	3.5 lit.
Oil Tank Capacity		4.22 U.S. pt., 3.55 Imp. pt.	2 lit.
Lubrication System		Forced pressure and dry sump	
Air Filtration		Paper element	