

## FRAME (Cont'd)

ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N-m (kgf-m, lbf-ft)	REMARKS
<b>REAR WHEEL/SUSPENSION:</b>				
Rear axle nut	1	18	93 (9.5, 69)	NOTE 7
Rear brake disc mounting bolt	4	8	42 (4.3, 31)	NOTE 8
Driven sprocket nut	5	12	108 (11.0, 80)	NOTE 7
Rear shock absorber mounting nut	2	10	42 (4.3, 31)	NOTE 7
Shock link nut (frame side)	1	10	59 (6.0, 43)	NOTE 7
Shock link nut (shock arm plate side)	1	10	42 (4.3, 31)	NOTE 7
Shock arm plate nut (swingarm side)	1	10	42 (4.3, 31)	NOTE 7
Swingarm pivot adjusting bolt	1	30	15 (1.5, 11)	See page 14-19
Swingarm pivot lock nut	1	30	64 (6.5, 47)	
Swingarm pivot nut	1	18	93 (9.5, 69)	NOTE 7
Drive chain slider bolt	2	6	9 (0.9, 6.5)	NOTE 8
<b>HYDRAULIC BRAKE:</b>				
Front brake master cylinder holder bolt	2	6	12 (1.2, 9)	
Front brake master cylinder cap screw	2	4	1 (0.15, 1.1)	
Brake lever pivot bolt	1	6	1 (0.1, 0.7)	
Brake lever pivot nut	1	6	6 (0.6, 4.3)	
Brake lever adjuster	1	5	4 (0.4, 2.9)	
Front brake switch screw	1	4	1 (0.12, 0.9)	
Right front brake caliper mounting bolt	2	8	31 (3.2, 23)	NOTE 8
Left front brake caliper pivot bolt	1	8	31 (3.2, 23)	NOTE 8
Left front brake caliper bolt (second master joint)	1	8	25 (2.6, 19)	NOTE 8
Caliper body B bolt	9	8	32 (3.3, 24)	NOTE 8
Front brake caliper slide pin (main)	3	12	23 (2.3, 17)	NOTE 2
Front brake caliper slide pin (sub)	3	8	13 (1.3, 9)	NOTE 2
Pad pin	3	10	18 (1.8, 13)	
Brake caliper bleeder	6	8	6 (0.6, 4.3)	
Second master cylinder mounting bolt	2	8	31 (3.2, 23)	NOTE 8
Second master cylinder push rod nut	1	8	18 (1.8, 13)	
Second master cylinder connector	2	6	10 (1.0, 7)	
Rear master cylinder mounting bolt	2	6	12 (1.2, 9)	
Rear master cylinder reservoir mounting bolt	1	6	12 (1.2, 9)	
Rear master cylinder push rod nut	1	8	18 (1.8, 13)	
Rear master cylinder hose joint screw	1	4	1 (0.15, 1.1)	NOTE 2
Brake hose oil bolt	12	10	34 (3.5, 25)	
Brake pipe joint	8	10	17 (1.7, 12)	NOTE 5
Brake pipe 2/3 way joint	2	6	12 (1.2, 9)	
Brake hose clamp bolt	2	6	12 (1.2, 9)	
Delay valve mounting bolt	2	6	12 (1.2, 9)	
PCV (Proportional Control Valve) mounting bolt	2	6	12 (1.2, 9)	
Right front brake hose clamp bolt	1	6	12 (1.2, 9)	
<b>IGNITION SYSTEM:</b>				
Ignition coil mounting nut	4	6	16 (1.6, 12)	
Ignition coil mounting nut	2	6	10 (1.0, 7)	
<b>LIGHTS/METERS/SWITCHES:</b>				
Ignition switch mounting bolt	2	8	25 (2.5, 18)	
Side stand switch mounting bolt	1	6	10 (1.0, 7)	