

Requisite Service

• Seat removal/installation(page 2-2)

• Tail cowl removal/installation(page 2-7)

Procedure		Q'ty	Remarks
Removal Order			
(1)	Bolt	3	
(2)	Left pillion step stay	1	
(3)	Turn signal light wire connector	2	
(4)	Bolt	3	
(5)	Rear fender A	1	
(6)	-screw	4	
(7)	-flange collar	4	
(8)	-seat rubber	4	
(9)	-rear turn signal light (right/left)	1/1	
(10)	-flange collar	4	
(11)	-turn signal light base (right/left)	1/1	
(12)	-nut	1	
(13)	-reflector	1	
(14)	Screw/washer	2/2	G, SW, AR type
(15)	Collar	2	
(16)	Washer	2	
(17)	Nut	2	
(18)	Rear fender C	1	
Installation Order			
(18)	Rear fender C	1	G, SW, AR type
(17)	Nut	2	
(16)	Washer	2	
(15)	Collar	2	
(14)	Screw/washer	2/2	
(13)	-retlector	1	
(12)	-nut	1	
(11)	-turn signal light base (right/left)	1/1	
(10)	-flange collar	4	
(9)	-rear turn signal light (right/left)	1/1	
(8)	-seat rubber	4	
(7)	-flange collar	4	
(6)	-screw	4	
(5)	Rear fender A	1	
(4)	Bolt	3	
(3)	Turn signal light wire connector	2	
(2)	Left pillion step stay	1	
(1)	Bolt	3	