

GENERAL INFORMATION

FRAME (Cont'd)				
ITEM	Q'TY	THREAD DIA. (mm)	TORQUE N·m (kgf·m, lbf·ft)	REMARKS
HYDRAULIC BRAKE:				
Brake hose oil bolt	4	10	34 (3.5, 25)	
Brake lever pivot bolt/nut	1/1	6	6 (0.6, 4.3)	
Brake lever adjuster lock nut	1	5	6 (0.6, 4.3)	
Front master cylinder reservoir cover screw	2	4	2 (0.2, 1.4)	
Front master cylinder holder bolt	2	6	10 (1.0, 7)	
Front caliper mounting bolt	2	8	29 (3.0, 22)	NOTE 1
Caliper bleed valve	2	8	6 (0.6, 4.3)	
Rear brake disc cover screw	2	6	7 (0.7, 5.1)	NOTE 1
Rear master cylinder mounting bolt	2	6	12 (1.2, 9)	
Brake pad pin	2	10	18 (1.8, 13)	
Brake pad pin plug	2	10	3 (0.3, 2.2)	
Front caliper pin bolt A	1	8	23 (2.3, 17)	NOTE 1
Front caliper bracket pin bolt	1	8	23 (2.3, 17)	NOTE 1
Rear caliper pin bolt	1	12	27 (2.8, 20)	
Rear caliper bracket pin bolt	1	8	13 (1.3, 9)	NOTE 1
Brake pedal pivot bolt	1	8	25 (2.6, 19)	
Rear master cylinder push rod lock nut	1	8	18 (1.8, 13)	